




نور عمان



NOOROMAN

ND10-562

Recessed Spotlight



It rotates about 25 degrees



Efficient heat dissipation Increase air convection



Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
ND10-56201	10W LED	3000K, 4000K, 5000K, 6000K	95-100	950-1000lm	RAL9016/RAL9005	Ø90xH50mm cutout 80mm
ND10-56202	10W LED	3000K, 4000K, 5000K, 6000K	95-100	950-1000lm	RAL9016/RAL9005	Ø82xH50mm cutout 75mm
ND10-56203	10W LED	3000K, 4000K, 5000K, 6000K	95-100	950-1000lm	RAL9016/RAL9005	90x90xH30mm cutout 80mm
ND10-56204	10W LED	3000K, 4000K, 5000K, 6000K	95-100	950-1000lm	RAL9016/RAL9005	82x82xH30mm cutout 75mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >80
Colour Consistency (SDCM) : 3
Beam Angle (°) : 24° 36°
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : COB
Life Time : L80 B20 50,000h
Nominal Life Time (h) : 50,000
Emergency: Possible on request
CCT Selection DIP Switch: YES

OPERATION AND CONNECTION

Driver Included : Yes
PF : ≥ 0.9
Operating Temperature (°C) : -25...+50
Max. Tc (°C) : 65
Dimmable : Optional - DALI / 1-10V

TECHNICAL DATA

Voltage Interval (V) : AC220-265
Line Frequency (Hz) : 50/60Hz

MEASUREMENT AND INSTALLATION

Operating Environment : Indoor / Outdoor
IP Degree of Protection : IP65
Installation : Recessed mounted

