




نور عمان




NOOROMAN

PROx

WP Industrial Light

Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
PROX WP 65010	10W LED	4000K, 5000K, 6500K	129	1290lm	RAL7035	L665xW76xH72mm
PROX WP 65020	12W LED	4000K, 5000K, 6500K	129	1550lm	RAL7035	L665xW76xH72mm
PROX WP 65030	15W LED	4000K, 5000K, 6500K	131	1970lm	RAL7035	L665xW76xH72mm
PROX WP 65040	18W LED	4000K, 5000K, 6500K	133	2390lm	RAL7035	L665xW76xH72mm
PROX WP 65050	22W LED	4000K, 5000K, 6500K	134	2940lm	RAL7035	L1165xW76xH72mm
PROX WP 65060	30W LED	4000K, 5000K, 6500K	133	4000lm	RAL7035	L1165xW76xH72mm
PROX WP 65460	46W LED	4000K, 5000K, 6500K	128	5880lm	RAL7035	L1165xW76xH72mm
PROX WP 65070	22W LED	4000K, 5000K, 6500K	133	2930lm	RAL7035	L1465xW76xH72mm
PROX WP 65080	27W LED	4000K, 5000K, 6500K	135	3650lm	RAL7035	L1465xW76xH72mm
PROX WP 65090	37W LED	4000K, 5000K, 6500K	136	5040lm	RAL7035	L1465xW76xH72mm
PROX WP 65490	58W LED	4000K, 5000K, 6500K	127	7360lm	RAL7035	L1465xW76xL72mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >95
Colour Consistency (SDCM) : 3
Beam Angle (°) : 110
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : 1
Life Time : L80 B20 50,000h
Nominal Life Time (h) : 50,000
Emergency: Possible on request
RG: 0

TECHNICAL DATA

Voltage Interval (V) : 220...240
Line Frequency (Hz) : 50, 60

MEASUREMENT AND INSTALLATION

Operating Environment : Indoor/Outdoor
IP Degree of Protection : IP66
Installation : Surface mounted, Wire-cable

OPERATION AND CONNECTION

Driver Included : Yes
Driver Model : Constant Current
Operating Temperature : -25...+55
Max. Tc (°C) : 85
Dimmable : Optional - DALI / 1-10V

CONSTRUCTION

Body : Polycarbonate
Diffuser : Polycarbonate

