




NC102 Downlight




NC102 slimline IP65 rotatable downlight adopts brand CREE COB, anti-glare lens and ADC12 aluminum heatsink. External driver is exchangeable through quick connector between non-dimmable driver and Triac dimmable driver.

-
-
-
-

Code	Watt	Size(AxBmm)	Cut-out(mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NC102A-2.5-5W	5W	Ø80x30	Ø68-72	530lm	0.24	50PCS
NC102A-2.5-8W	8W	Ø80x30	Ø68-72	815lm	0.24	50PCS
NC102B-2.5-10W	10W	Ø90x39.3	Ø75-80	1000lm	0.25	50PCS
NC102-3-10W	10W	Ø110x49.5	Ø90-95	1000lm	0.40	30PCS
NC102-3-13W	13W	Ø110x49.5	Ø90-95	1350lm	0.40	30PCS



ND103 Downlight



ND103 slimline IP65 fxd downlight adopts brand CREE COB, anti-glare lens and ADC12 aluminum heatsink. External driver is exchangeable through quick connector between non-dimmable driver and Triac dimmable driver.

-
-
-
-

Code	Watt	Size(AxBmm)	Cut-out(mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
ND103A-2.5-5W	5W	Ø80x40	Ø68-72	530lm	0.18	50PCS
ND103A-2.5-8W	8W	Ø80x40	Ø68-72	815lm	0.18	50PCS
ND103B-2.5-10W	10W	Ø90x49.4	Ø75-80	1000lm	0.27	50PCS
ND103-3-10W	10W	Ø110x64.3	Ø90-95	1000lm	0.45	30PCS
ND103-3-13W	13W	Ø110x64.3	Ø90-95	1350lm	0.45	30PCS