


NG-AA

Panel light



NG-AA backlit troffer is anti-glare design, the compact and seamless splicing make it a great looking .It adopts anti-glare prism plate to reach UGR<19,could be interchangeable CCT (3000K+4000K+5700K) with slide switch.

IP40

UGR<19

DIM

DALI

0-10V

TUNABLE WHITE

SLIDE SWITCH 3 in 1

AC 220-240V

PF≥0.9

CRI≥80

TP(b)

SAA


RoHS

CE

Code	Watt	Size(AxBxCmm)	Cut-out(±5mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NG6060-36W-AA	36W	595x595x40	580x580	3700lm	2.60	5PCS
NG30120-36W-AA	36W	1195x295x40	1180x280	3700lm	2.99	5PCS
NG6262-36W-AA	36W	620x620x49	605x605	3700lm	2.73	5PCS
NG60120-60W-AA	60W	1195x595x49	1180x580	6500lm	5.41	2PCS

NG-N

Troffer light



NG-N is troffer light with external driver, adopts secondary optical designed and special treatment diffuser to achieve more uniform and softer light, providing more comfortable visual experience. Luminous efficiency 105lm/W. Powder spraying surface treatment is employed in the lamp fxture which makes the lamp corrosion resistant. Designed for grid ceiling commercial applications.

IP40

DIM

DALI

0-10V

SLIDE SWITCH 3 in 1

AC 220-240V

PF≥0.9

CRI≥80

SAA

RoHS

CE

Code	Watt	Size(AxBxCmm)	Cut-out(±5mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NG6060-33W-N	33W	595x595x54	580x580	3850lm	2.50	5PCS
NG30120-33W-N	33W	1195x295x54	1180x280	3850lm	2.70	5PCS