




NC103

COB Downlight



NC103 fxd downlight adopts brand CREE COB, reflector and ADC12 aluminum heatsink. Deep cone design creates low UGR. External driver is exchangeable through quick connector among non-dimmable driver, Triac dimmable, 0-10V and DALI dimmable drivers.

- 60°
 IP20
- DIM DALI 0-10V
- AC 200-240V PF≥0.9 CRI≥80 CRI≥90 CRI≥97
- SAA RoHS CE

Code	Watt	Size(AxBmm)	Cut-out(mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NC103-3-12W	12W	Ø100x90.6	Ø90-95	1010lm	0.40	24PCS
NC103-3-12W-D	12W	Ø100x90.6	Ø90-95	980lm	0.40	24PCS


CCT 3000K 4000K 5000K 5700K

Trim White Black



NC103B

SMD Downlight



NC103B fxd downlight adopts high efficiency SMD LED chips, PMMA lens and ADC12 aluminum heatsink. Deep cone design creates low UGR. External driver is exchangeable through quick connector among non-dimmable driver, Triac dimmable, 0-10V and DALI dimmable drivers.

- 60°
 IP20 IP54
- DIM DALI 0-10V
- AC 200-240V PF≥0.9 CRI≥80 CRI≥90 CRI≥97
- SAA RoHS CE

Code	Watt	Size(AxBmm)	Cut-out(mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NC103B-2.5-8W	8W	Ø80x100	Ø70-75	720lm	0.38	24PCS
NC103B-2.5-10W	10W	Ø80x100	Ø70-75	900lm	0.38	24PCS
NC103B-3-10W	10W	Ø100x90.6	Ø90-95	960lm	0.40	24PCS
NC103B-3-12W	12W	Ø100x90.6	Ø90-95	1140lm	0.40	24PCS

CCT 3000K 4000K 5000K 5700K

Trim White Black