




نور عمان



NOOROMAN

PROXY

Ceiling / Wall Bulkhead Light

Item	Power	CCT	LM/W	Lumen	Finish	Dimensions
PX10	10W LED	3000K, 4000K, 5000K, 6000K, 6500K	97-103	970-1030lm	RAL9016/RAL9005	W275xH80mm
PX15	15W LED	3000K, 4000K, 5000K, 6000K, 6500K	97-102	1450-1530lm	RAL9016/RAL9005	W275xH80mm
PX20	20W LED	3000K, 4000K, 5000K, 6000K, 6500K	97-105	1940-2100lm	RAL9016/RAL9005	W275xH80mm
PX25	25W LED	3000K, 4000K, 5000K, 6000K, 6500K	96-105	2420-2625lm	RAL9016/RAL9005	W275xH80mm
PX30	30W LED	3000K, 4000K, 5000K, 6000K, 6500K	96-105	2900-3150lm	RAL9016/RAL9005	W275xH80mm



LIGHT TECHNICAL DATA

Light Source : LED
Light Source Included : Yes
Replaceability : Replaceable LED by professional,
Replaceable Control gear by professional
Colour Rendering Index (Ra) : >80
Colour Consistency (SDCM) : 3
Beam Angle (°) : 110
Light sharing : Symmetric
Light Outlet : Direct
Number of Lamps (pcs) : SMD
Life Time : L80 B20 50,000h
Emergency: Possible on request

TECHNICAL DATA

Voltage Interval (V) : AC220...240
Line Frequency (Hz) : 50/60Hz

MEASUREMENT AND INSTALLATION

Operating Environment : Outdoor
IP Degree of Protection : IP65 IK10
Installation : Wall mounted / Ceiling mounted



OPERATION AND CONNECTION

Driver Included : In-Built
Operating Temperature (°C) : -20...+50
Power Factor: >0.9
Max. Tc (°C) : 65
Dimmable : Optional - DALI / 1-10V

CONSTRUCTION

Body : Die-cast Aluminium
Diffuser : UV Stabilized PC
No IR or UV radiation
Vandal Proof rated
Multi-function, classic design, easy adapted for many-applications

Diffuser cover options



Photometrics

