


NL-AK

Panel light



NL-AK panel light is a module design with external driver, featuring PC louver reflectors to help reduce UGR, offers the ideal combination of stylish design and optimum performance for both task and general lighting; Module replaceable, easy to install and maintain.Available in various installation ways: recessed, suspended and surface mounted, and can replace the traditional panel light.

IP40

DALI

0-10V

AC 220-240V

PF≥0.9

CRI≥80

SAA


RoHS

CE

Code	Watt	Size(AxBxCmm)	Cut-out(±5mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NL3060-18W-AK	18W	595x295x36	580x280	2010lm	1.55	4PCS
NL6060-25W-AK	25W	595x595x36	580x580	3552lm	2.90	4PCS
NL6060-30W-AK	30W	595x595x36	580x580	3660lm	2.90	4PCS
NL6060-36W-AK	36W	595x595x36	580x580	3900lm	2.90	4PCS
NL6262-36W-AK	36W	620x620x36	605x605	3900lm	3.30	4PCS
NL30120-36W-AK	36W	1195x295x36	1180x280	3920lm	2.95	4PCS

NL-008

Panel light



NL008 panel light is direct lighting with louver anti-glare design with external driver, adopting high lumen SMD led and special lens which provide high light efficiency and uniform light output, CCT switchable is available, it is a ideal replacement for traditional 3*24W HO T5 and 3*18W T8 fuorescent louver luminaries and side lit LED panel light.

IP40

AC 200-240V

PF≥0.9

CRI≥80

SAA

RoHS

CE

Code	Watt	Size(AxBxCmm)	Cut-out(±5mm)	Lumen(±5%)	N.W/pc(kgs)	Q'ty/CTN
NL008-3060	15W	295x595x32	270x570	1800lm	2.00	5PCS
NL008-6060	30W	595x595x32	570x570	3600lm	3.20	5PCS
NL008-30120	30W	295x1195x32	270x1170	3600lm	3.60	5PCS
NL008-60120	60W	595x1195x32	570x1170	7200lm	6.00	4PCS